SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product nameRECHARGEABLE LI-ION BATTERY ZXAA (1.5V/3.7V 2400MAH/880MAH 3.0WH)SynonymsRECHARGEABLE LI-ION BATTERY ZXAA

1.2 Uses and uses advised against

Uses LITHIUM ION BATTERY • RECHARGEABLE BATTERY

1.3 Details of the supplier of the product

Supplier name WHITE INTERNATIONAL NZ LIMITED

Address 15G Kerwyn Ave, East Tamaki, AUCKLAND, 2013, NEW ZEALAND

Telephone 0800 509 506

Email sales@whiteint.co.nz

1.4 Emergency telephone numbers

Emergency +64 21 143 2359

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NON HAZARDOUS ACCORDING TO NZ ENVIRONMENTAL PROTECTION AUTHORITY CRITERIA

2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

Do not short circuit, recharge, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion. The Lithium batteries described in this Safety Data Sheet are sealed units which are not hazardous when used according to the recommendations of the manufacturer.

Under normal conditions of use, the electrode materials and liquid electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Exposure may occur as a result of external environmental conditions or in cases of abuse (mechanical, thermal, electrical) which lead to the activation of safety pressure relief valve(s) and/or cause a rupture of the battery container. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances. The mixture inside the article has the following hazardous characteristics:

May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

NEW ZEALAND: Batteries are considered to be manufactured articles and are not, therefore, covered by the HSNO Act. Although they may contain hazardous substances, the item has an end use function wholly dependent on its shape and design, which does not involve the intentional release of any hazardous component. Also, the primary function of the article does not lead to any (HSNO) hazardous effect. Hazards arising during transport will still be controlled, as the local transport legislation picks up the international requirements. Disposal issues will be covered by the MfE hazardous waste programme and local authority requirements.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
COBALT LITHIUM DIOXIDE	12190-79-3	235-362-0	32%



GRAPHITE	7782-42-5	231-955-3	26%
COPPER	7440-50-8	231-159-6	9%
ALUMINIUM POWDER (STABILISED)	7429-90-5	231-072-3	7%
NICKEL	7440-02-0	231-111-4	3%
POLYVINYL CHLORIDE (PVC)	9002-86-2	618-338-8	3%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye Exposure is considered unlikely unless casing is damaged. Flush gently with running water. Seek medical attention if irritation develops.

Inhalation Exposure is considered unlikely. Due to product form / nature of use, an inhalation hazard is not anticipated.

Skin Exposure is considered unlikely unless casing is damaged. Gently flush affected areas with water. Seek medical attention if irritation develops.

Ingestion For advice, contact the National Poisons Centre on 0800 764 766 (0800 POISON) or +643 479 7248 or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities Eye wash facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

Adverse effects not expected from this product during normal use. However, exposure to battery contents may cause irritation and potential burns.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent. Do NOT use water. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Contents react with water. May explode if exposed to high temperatures due to pressure build up in battery casing. Lithium may burn in a fire situation and may be ejected from the battery. Damaged cells may evolve toxic and flammable vapours.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

- 2Y
- 2 Fine Water Spray.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible. If battery is broken or damaged, absorb liquid with sand or similar. Contain spillage, then collect and place in suitable containers for disposal. CAUTION: Avoid exposure to contents. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE



7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store tightly sealed in a cool, dry, well ventilated area, removed from water, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Store between 15°C and 25°C.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
ingreatent	Reference	ppm	mg/m³	ppm	mg/m³
Aluminium metal and insoluble aluminium compounds (including pyro powder, aluminium oxide, and aluminium welding fumes), as Al	WES [NZ]		1		
Copper and its inorganic compounds, as Cu	WES [NZ]		0.01		
Copper and its inorganic compounds, as Cu	WES [Proposed]		0.01		
Graphite, all forms except graphite fibres	WES [NZ]		3		
Nickel, elemental or metallic	WES [NZ]		0.005		
Nickel, inorganic compounds	WES [NZ]		0.05		
Nickel, inorganic compounds (respirable dust)	WES [NZ]		0.005		

Biological limits

Ingredient	Determinant	Sampling Time	BEI
COBALT LITHIUM DIOXIDE	Cobalt in urine	End of shift at	15 µg/L
		end of workweek	

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas.

PPE

Eye / Face	Wear safety goggles if handling a ruptured or leaking battery cell.
Hands	Wear neoprene or nitrile gloves if handling a ruptured or leaking battery cell.
Body	Not required under normal conditions of use.
Respiratory	In case of battery or cell rupture, use a self-contained full face respiratory mask.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	SOLID (BATTERY)
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	NOT AVAILABLE

ChemAlert.

9.1 Information on basic physical and chemical properties

Vapour density	NOT AVAILABLE
Relative density	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

No information provided.

10.5 Incompatible materials

Battery contents are incompatible with water (evolving flammable gas), oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Batteries consist of a hermetically sealed metallic container containing a number of chemicals and materials of construction that may be hazardous upon release. Over exposure considered unlikely unless battery ruptures and contact with contents occurs. Contents may be harmful.

Information available for the ingredients:

Ingredient		Oral LD50	Dermal LD50	Inhalation LC50
COPPER			> 2000 mg/kg (rat)	
NICKEL		> 9000 mg/kg (Sprague-Dawley rat)		
Skin	Battery contents may be corrosive and cause irritation, redness, dermatitis and possible skin burns. Exposure is considered unlikely unless the battery ruptures.			
Eye	Battery contents may be corrosive and cause irritation, redness and possible eye burns. Exposure is considered unlikely unless the battery ruptures.			
Sensitisation	Exposure to contents may cause skin sensitisation.			
Mutagenicity	No evidence of mutagenic effects.			
Carcinogenicity	Due to the product encapsulation, exposure to contents is not anticipated with normal use. However, the battery contains contents which may be carcinogenic.			
Reproductive	Exposure to contents containing cobalt may damage fertility or the unborn child.			
STOT - single exposure	Not classified as causing organ damage from single exposure. Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures. Exposure to contents may cause respiratory irritation.			
STOT - repeated	Due to the product form and	nature of use, exposure to	internal contents is not anti-	cipated unless the battery

ChemAlert.

exposure

ruptures. Some battery contents have the potential to cause damage through repeated exposure, however such exposure is considered unlikely.

Aspiration

such exposure is considere Not relevant.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

This product is not readily biodegradable.

12.3 Bioaccumulative potential

Limited information was available at the time of this review.

12.4 Mobility in soil

This product has low mobility in soil.

12.5 Other adverse effects

Avoid contamination of drains and waterways.

13. DISPOSAL CONSIDERATIONS


13.1 Waste treatment methods

 Waste disposal
 Reuse or recycle where possible. Return to manufacturer/supplier. Contact your state EPA or the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005, IMDG AND IATA



	LAND TRANSPORT (NZS 5433)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3480	3480	3480
14.2 Proper Shipping Name	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	LITHIUM ION BATTERIES (including lithium ion polymer batteries)	LITHIUM ION BATTERIES (including lithium ion polymer batteries)
14.3 Transport hazard class	9A	9A	9A
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Marine Pollutant.

14.6 Special precautions for user

2Y F-A, S-I

Hazchem code	
EmS	
Other information	

The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969). Cells and batteries offered for transport are not subject to the provisions of the Australian Dangerous Goods code if they meet the criteria of UN Special Provision 188 (SP 188). UN number 3481 applies for LITHIUM BATTERIES CONTAINED IN EQUIPMENT or LITHIUM BATTERIES PACKED WITH EQUIPMENT which may also apply to this product.



15. REGULATORY INFORMATION

Approval code	MANUFACTURED ARTICLE
Group standard	Something for which its intended use is primarily to do with its physical shape, rather than its chemica composition.
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt. NEW ZEALAND: NZIOC (New Zealand Inventory of Chemicals) All components are listed on the NZIOC inventory, or are exempt. UNITED STATES: TSCA (US Toxic Substances Control Act) All components are listed on the TSCA inventory, or are exempt.

16. OTHER INFORMATION

Additional information EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, ENGINEERING CONTROLS are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



PRODUCT NAME	RECHARGEABLE LI-ION BATTERY ZXAA (1.5V/3.7V 2400MAH/880MAH 3.0WH)		
Abbreviations	ACGIH CAS # CCID CNS EC No. EMS EPA GHS HSNO IARC LC50 LD50 mg/m ³ OEL pH ppm STEL STOT-RE STOT-RE	American Conference of Governmental Industrial Hygienists Chemical Abstract Service number - used to uniquely identify chemical compounds Chemical Classification and Information Database (HSNO) Central Nervous System EC No - European Community Number Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) Environmental Protection Authority [New Zealand] Globally Harmonized System Hazardous Substances and New Organisms International Agency for Research on Cancer Lethal Concentration, 50% / Median Lethal Concentration Lethal Dose, 50% / Median Lethal Dose Milligrams per Cubic Metre Occupational Exposure Limit relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). Parts Per Million Short-Term Exposure Limit Specific target organ toxicity (repeated exposure) Specific target organ toxicity (single exposure)	
	TLV TWA	Threshold Limit Value Time Weighted Average	
Report status	product and s It is based manufactures the current s at the time of	ent has been compiled by RMT on behalf of the manufacturer, importer or supplier of the serves as their Safety Data Sheet ('SDS'). on information concerning the product which has been provided to RMT by the r, importer or supplier or obtained from third party sources and is believed to represent tate of knowledge as to the appropriate safety and handling precautions for the product of issue. Further clarification regarding any aspect of the product should be obtained the manufacturer, importer or supplier.	
	not provide a no liability fo	has taken all due care to include accurate and up-to-date information in this SDS, it does any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts or any loss, injury or damage (including consequential loss) which may be suffered or any person as a consequence of their reliance on the information contained in this SDS.	
Prepared by	5 Ventnor Äv Western Aus Phone: +61 & Fax: +61 8 9	3 9322 1711 322 1794 rmtglobal.com	
		[End of SDS]	